IM 2500/IM 3000/IM 3500

MAIN SPECIFICATIONS

	IM 2500	IM 3000	IM 3500
GENERAL			
Warm-up time	18 seconds	17.7 seconds	18.6 seconds
First copy speed: BW	4.1 seconds	3.9 seconds	3.8 seconds
Continuous output speed	25 ppm	30 ppm	35 ppm
Memory: maximum		2 GB	
SSD: maximum		256 GB	
ARDF capacity		100 sheets	
Weight		71 kg	
Dimensions: W x D x H		587 x 673 x 913 mm	
Power source		220 - 240 V, 50 - 60 Hz	
COPIER			
Multiple copying		Up to 999 copies	
Resolution		600 dpi	
Zoom		From 25% to 400% in 1% steps	
PRINTER			
CPU		Intel® Atom Processor ApolloLake-I GHz	
Printer language: standard		PCL5e, PCL6, PostScript 3 (emulation), PDF direct (emulation)	
Printer language: option		Genuine Adobe®, PDF Direct from Adobe®	
Print resolution: maximum		1,200 x 1,200 dpi	
Network interface: standard		Ethernet 10 base-T/100 base-TX/1000 base-T, USB Host I/F Type A, USB Device I/F Type B	
Network interface: option		Bi-directional IEEE 1284, Additional NIC (2nd port), Wireless LAN (IEEE 802.11 b/g/n)	
Mobile printing capability		Apple AirPrint, Mopria®, NFC, Ricoh Smart Device Connector	
Windows® environments		Windows® 8.1, Windows® 10, Windows® Server 2012, Windows® Server 2012R2, Windows® Server 2016, Windows® Server 2019	
Mac OS environments		Macintosh OS X v10.13 or later	
UNIX environments		UNIX Sun® Solaris, HP-UX, SCO OpenServer, RedHat® Linux, IBM® AIX, Citrix XenApp (7.6 LTSR, 7.15 LTSR, VirtualApps/Desktops 7 1912 LTSR and later)	
SAP® environments		SAP® R/3®, SAP® S/4®	
Other supported environments		NDPS Gateway, AS/400® using OS/400 Host Print Transform	
SCANNER			
Scanning speed: ARDF (A4 LEF, B&W full colour)		80 ipm (200-300 dpi)	
Resolution: maximum		1,200 dpi	
File formats		Single Page TIFF, Single page JPEG, Single page PDF, Single page High compression PDF, Single page PDF/A, Multi page TIFF, Multi page PDF, Multi page High compression PDF, Multi page PDF/A	
Scan modes		E-mail, USB, SD Card, URL, FTP, SMB	
FAX			
Circuit		PSTN, PBX	
Transmission speed		3 seconds	
Modem speed: maximum		33.6 Kbps	
Resolution: standard		8x3.85 line/mm, 200x100 dpi 8x7.7 line/mm, 200x200 dpi	
Resolution: option		16x15.4 line/mm, 400x400 dpi	
Compression method		MH, MR, MMR, JBIG	
Memory: standard		4 MB (320 pages)	
Memory: maximum		60 MB (4,800 pages)	
PAPER HANDLING			
Recommended paper size		Standard paper tray(s): A3, A4, A5, A6, B4, B5, B6, Envelopes Optional paper tray(s) : A3, A4, A5, A6, B4, B5, B6, Envelopes Bypass tray: A3, A4, A5, A6, B4, B5, B6, Envelopes, Custom Size paper: Width: 90 mm - 304.8 mm, Length: 148 mm - 600 mm	
Paper input: standard		1,200 sheets	
Paper input: maximum		3,200 sheets	
Paper output: standard		500 sheets	
Paper output: max.		1,625 sheets	
Paper weight: standard		Trays: 60 - 300 g/m² Bypass: 52 - 300 g/m² Duplex: 52 - 256 g/m²	
Paper types		Plain paper, Recycled paper, Special paper, Colour paper, Letterhead, Cardstock, Preprinted paper, Bond paper, Coated paper, Envelope, Label paper, OHP	

IM 2500/IM 3000/IM 3500

MAIN SPECIFICATIONS

	IM 2500	IM 3000	IM 3500
ECOLOGY			
Power consumption: max.		< 1,600 W	
Power consumption: operation	446 W	475 W	553 W
Power consumption: ready		56.4 W	
Power consumption: sleep	0.77 W	0.77 W	0.78 W
TEC*	0.32 kWh/week	0.38 kWh/week	0.44 kWh/week
* It is a reference value based on the ENERGY STAR Ver.3.0 test method.			

INPUT/OUTPUT TRAYS AND FINISHER OPTIONS

1x 550-sheet paper tray, 2x 550-sheet paper tray, 2,000-sheet Large capacity tray, 1,000-sheet Hybrid finisher, 500-sheet Internal finisher, Internal shift tray, One-bin tray

OTHER OPTIONS

Fax unit, Fax memory unit, Cabinet, Caster table, Memory unit, Side Tray, Punch units, Bi-directional IEEE 1284, IEEE 802.11 a/g/n, File format converter, OCR unit, ADF handle, External keyboard bracket, Counter I/F unit, Key counter bracket, Smart card reader built-in unit, Bridge unit

CONSUMABLES

Toner (black)	24,000 prints
Consumable yield based on 5% coverage/A4	

For availability of models, options and software, please consult your local supplier.

RICOH
imagine. change.

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The images in this brochure are not real photographs and slight differences in detail might appear, including in relation to colour. Not all services and solutions are available to all customers. Copyright © 2026 Ricoh Europe PLC. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Europe PLC.